

Custom Dynamics® Shark Demon® 2 LED Off Road Auxiliary Light Harness Installation Instructions



Part Numbers

SD2-OR-Y-HARN

Package Contents

SD2-OR-Y-HARN Harness (1)
Solder Seal Sleeves (15)
Female Spade Terminals (3)
Rubber Insulators (3)
Instructions (1)



Fitment

Universal 12VDC negative ground systems, SXS & UTV.

Note

Use with SD2-OR-W, SD2-OR-Y LED Off Road Auxiliary Lights (**sold separately**) and CD-OR-SWITCH Rocker Switch (**sold separately**).

Suggested Tools

Safety Glasses
Wire Strippers/Crimping Tool
Heat Gun

Installation

Warning

Rider and passenger safety depend upon the correct installation of this kit. Use the appropriate service manual procedures. If the procedure is not within your capabilities or you do not have the correct tools, have a qualified technician perform the installation. Improper installation of this kit could result in death or serious injury.

1. Remove all necessary parts to disconnect the negative battery cable from the battery.
2. Connect the SD2-OR-Y-HARN Harness red, black and white wires to the Shark Demon® 2 LED Off Road Auxiliary Lights red, black and white wires using the supplied Solder Seal Sleeves. Up to 5 SD2 LED Off Road Auxiliary Lights can be used. Shown in **Figure 1**.
3. Find a suitable location for the CD-OR-SWITCH (**sold separately**). Use the supplied Female Spade Terminals to connect SD2-OR-Y-HARN to the CD-OR-SWITCH. Shown in **Figure 1**. Refer to CD-OR-SWITCH installation instructions for proper operation.

Note

Rubber Insulators for the Female Spade Terminals must be installed to wire before crimping.

4. Use cable ties to secure all wires from being cut, frayed or pinched.
5. Make sure the SD2-OR-Y-HARN Harness wires are free and easily accessible for the Shark Demon® 2 LED Off Road Auxiliary Light to be connected. Refer to the Custom Dynamics® Shark Demon® 2 Off Road LED Light (**sold separately**) installation instructions for installation. All wiring connections shown in **Figure 1**.

Questions? Email: Info@CustomDynamics.com or Call us at: 1(919)554-0949 M-TH 8:30AM-5:30PM, F 9:30AM-5:30PM EST

