

Custom Dynamics® Taillight Baseplate Installation Instructions



Part Numbers

TL-BASEPLATE-BLACK, TL-BASEPLATE-CHROME

Package Contents

Custom Dynamics® Taillight Baseplate (1)
Instructions (1)



Fitment

2000-2024 Harley-Davidson® OEM Fenders with P/N: 68296-99A.

Suggested Tools

Safety Glasses
Phillips Screwdriver

Installation

Warning

Rider and passenger safety depend upon the correct installation of this kit. Use the appropriate service manual procedures. If the procedure is not within your capabilities or you do not have the correct tools, have a qualified technician perform the installation. Improper installation of this kit could result in death or serious injury.

1. Remove all necessary parts to disconnect the negative battery cable from the battery.
2. Remove the OEM taillight by removing the two Phillips screws, save for reuse, and unplug from the taillight circuit board.
3. Unplug all remaining connectors from the taillight circuit board.
4. Remove the large Phillips head screw in the center of the OEM baseplate and save for reuse. Pull the remaining connectors through the OEM taillight baseplate opening and remove baseplate from motorcycle.
5. Remove the taillight circuit board from the OEM taillight baseplate and install onto the new Custom Dynamics® Taillight Baseplate.
6. Install the new Custom Dynamics® Taillight Baseplate to the fender, route the wire harness through the opening in the baseplate and reinstall the large Phillips head screw and tighten.
7. Plug in all connectors into the appropriate connections and plug in new Custom Dynamics® or ProBEAM® LED Taillight by reusing the two Phillips head screws.

Note

DO NOT overtighten or use thread locker it will weaken the plastic at the screw holes and crack and the warranty will be voided.

8. Reconnect the negative battery cable to the battery and reinstall all necessary parts.
9. Test the new Custom Dynamics® or ProBEAM® LED Taillight with Custom Dynamics® Taillight Baseplate for proper operation.

Questions? Email: Info@CustomDynamics.com or Call us at: 1(919)554-0949 M-TH 8:30AM-5:30PM, F 9:30AM-5:30PM EST